



# Macon

# Macon

**MATERIAL MATIÈRE MATERIAL**

SS = Stainless steel **Inox**


**SIZE DIMENSIONS DIMENSIONES**

From DN 25 to 100 mm


**THREAD FILETAGE ROSCA**

MACON


**MALE PART NEZ FILETÉ**




**FEMALE PART PIÈCE LISSE**



**NUT ECROU**



**GASKET JOINT DE RACCORD**



DN	D	F	c
40	43	M55x3	4,5
50	53	M67x3	4,5
60	63	M79x3,5	4,5
70	73	M90x3,5	4,5
80	83	M102x4	4,5
100	103	M125x4	4,5

D	A	c
43	50	4,5
53	62,5	4,5
63	74	4,5
73	85	4,5
83	97	4,5
103	119	4,5

A	L	F
70	24	M55x3
79	24	M67x3
94	24	M79x3,5
105	24	M90x3,5
117	26	M102x4
140	26	M125x4

A	P	S
49	42	3,5
61	52	3,5
72	62	3,5
84	72	3,5
98	82	3
118	102	3

MACON	ØA	ØB
40	50,8	55
50	63	67
60	75	79
70	85	90
80	97,2	102
100	119	125






AL = Aluminium BR = Brass Laiton Latón ST = Steel Acier Acero SS = Stainless steel Inox PP = Polypropylene

# Trelleborg Fittings

		ID coupling Diam. raccord Diam. racor	ID shank Diam. douille Diam. espiga	Ref.	Notes	
 <p>Female. Serrated hose shank. For circlip. <b>Femelle. Douille crantée. Pour jonc.</b> <i>Hembra. Caña acanalada. Para anillo.</i></p>	<p>PAGE 99. Circlip and ferrule. <b>Jupe et jonc.</b> <i>Junta y anillo.</i></p>	SS 316L	43	38	011 70 02	
			53	51	011 70 04	
			63	63	011 70 00	
			73	70	510 04 61	
			73	76	011 70 06	
			83	76	011 70 25	
			103	101,5	011 70 11	
 <p>Male. Serrated hose shank. For circlip. <b>Mâle. Douille crantée. Pour jonc.</b> <i>Macho. Caña acanalada. Para anillo.</i></p>	<p>PAGE 99. Circlip and ferrule. <b>Jupe et jonc.</b> <i>Junta y anillo.</i></p>	SS 316L	43	38	011 70 01	
			53	51	011 70 03	
			63	63	011 69 99	
			73	70	510 04 62	
			73	76	011 70 05	
			83	76	011 70 26	
			103	101,5	011 70 07	
 <p>Nut. <b>Ecrou.</b> <i>Tuerca.</i></p>		SS 304	43	38	011 69 46	
			53	51	011 69 49	
			63	63	011 69 98	
			73	70	011 69 52	
			83	76	011 70 22	
			103	101,5	011 70 07	
			 <p>Gasket. For female MACON. <b>Joint. Pour femelle MACON.</b> <i>Junta. Para hembra MACON.</i></p>		NR	43
53		510 05 89				
63		510 05 90				
73		510 05 91				
83		510 05 92				
103		510 05 93				

AL = Aluminium BR = Brass Laiton Latón ST = Steel Acier Acero SS = Stainless steel Inox PP = Polypropylene

## Trelleborg Fittings

		ID coupling Diam. raccord Diam. racor	ID shank Diam. douille Diam. espiga	Ref.	Notes
	Spanner. Clé de serrage. Llave de presion.	SS 304		510 15 43	
	Female. Serrated hose shank. With collar. Femelle. Douille crantée. A collerette. Hembra. Caña acanalada. Con cuello.	SS 304	43	38	510 23 57
			53	50	510 23 53
			63	63	510 23 58
	Male. Serrated hose shank. With collar. Mâle. Douille crantée. A collerette. Macho. Caña acanalada. Con cuello.	SS 304	43	38	510 23 62
			53	50	510 23 63
			63	63	510 23 64
	Female for welding. Femelle à souder. Hembra para soldar.	SS 316L	43	43	510 23 18
			53	53	510 23 19
			63	63	510 23 20
			73	73	510 23 21
			83	83	510 23 22
	Male for welding. Mâle à souder. Macho para soldar.	SS 316L	103	103	510 23 23
			43	43	510 23 24
			53	53	510 23 25
			63	63	510 23 26
			73	73	510 23 27
			83	83	510 23 28